




版次 (Version)	变更内容 (Rev. Content)	变更者 (Change Person)



PCB LAYOUT



产品命名编码:
(Product Number Code):

FPH1.5-XX-350-02F-YY

系列 (Series)

极数 (NO. of poles)

端子间距 (Pitch)

型号 (Model)

塑体颜色 (Housing Color)

- | | |
|---------------|----------------------|
| 1:绿色 (Green) | 7:透明色 (Transparent) |
| 2:蓝色 (Blue) | 8:白色 (White) |
| 3:黑色 (Black) | 9:黄色 (Yellow) |
| 4:灰色 (Grey) | Y:多种颜色 (Mixed color) |
| 5:橙色 (Orange) | |
| 6:红色 (Red) | |

技术参数 (Technical Data)

应用组别 (Use group)	B	C	D
UL 额定电器参数 (Rated Electrical Parameters)	300V/8A	300V/8A	300V/8A
IEC 过压类别 (Overvoltage Category) / 污染等级 (Pollution Degree)	III/3	III/2	III/2
IEC 额定电器参数 (Rated Electrical Parameters)	320V/10A	300V/8A	300V/8A
压线范围 (Wire Range)	/		
工频耐压 (Frequency Voltage)	AC 1300V		
冲击耐压 (Rated Surge Voltage)	4000V		
绝缘阻抗 (Insulation Resistance)	DC500V 500MΩ above		
接触电阻 (Contact Resistance)	≤20mΩ		
剥线长度 (String Length)	/		
工作温度 (Temperature)	-40° C--+105° C		
额定扭矩 (Rated torque)	/		
材质和电镀 (Material and plating)			
绝缘材质 (Housing)	PA66 UL94V-0		
导体材料 (Contact)	铜合金, 镀锡 (Copper alloy, Sn plsted)		
/	/		

P=3.50mm, N为孔位数 (N for hole digits), 有效位数为 (Significant Digits): 02p-24p

N	02P	03P	04P	05P	06P	07P	08P	09P	10P	11P	12P	13P
L	10.70	14.20	17.70	21.20	24.70	28.20	31.70	35.20	38.70	42.20	45.70	49.20
B	3.50	7.00	10.50	14.00	17.50	21.00	24.50	28.00	31.50	35.00	38.50	42.00
N	14P	15P	16P	17P	18P	19P	20P	21P	22P	23P	24P	
L	52.70	56.20	59.70	63.20	66.70	70.20	73.70	77.20	80.70	84.20	87.70	
B	45.50	49.00	52.50	56.00	59.50	63.00	66.50	70.00	73.50	77.00	80.50	

 东莞市澳斯电子有限公司 DONGGUAN AOSI ELECTRONICS CO., LTD,	公差范围 (Tolerance Range)	
	150~	±1.50
型号 (Type): FPH1.5-XX-350-02F-YY	60~150	±1.00
	30~60	±0.60
核准 (Approval):	6~30	±0.40
	0~6	±0.25
核审 (Audit):	角度 (Angle)	X ±2°
	单位 (Units): mm	页码 (Page): 1/1
设计 (Design)	X.X	±1°
	比例 (Scale): FULL	版次 (Version): T0