




| 版次 (Version) | 变更内容 (Rev. Content) | 变更者 (Change Person) |
|-----------------|------------------------|------------------------|
| | | |
| | | |



| 技术参数 (Technical Data) | | | | |
|-----------------------------|---|----------------------------------|---------|------|
| UL | 应用组别(Use group) | B | C | D |
| | 额定电器参数 (Rated Electrical Parameters) | / | / | / |
| IEC | 过压类别(Overvoltage Category) /污染等级(Pollution Degree) | III/3 | III/2 | II/2 |
| | 额定电器参数 (Rated Electrical Parameters) | 250V/6A | 100V/4A | / |
| 压线范围(Wire Range) | | 24~20AWG 0.2~0.5MM ² | | |
| 工频耐压(Frequency Voltage) | | AC 1600V | | |
| 冲击耐压(Rated Surge Voltage) | | 2500V | | |
| 绝缘阻抗(Insulation Resistance) | | DC500V 500MΩ above | | |
| 接触电阻(Contact Resistance) | | ≤20mΩ | | |
| 剥线长度(String Length) | | 8~9 (mm) | | |
| 工作温度(Temperature) | | -40° C~+105° C | | |
| 额定扭矩(Rated torque) | | / | | |
| 材质和电镀(Material and plating) | | | | |
| 绝缘材质(Housing) | | PA66 UL94V-0 | | |
| 导体材料(Contact) | | 铜合金, 镀锡(Copper alloy, Sn plated) | | |
| / | | / | | |


产品命名编码:
(Product Number Code):



- | | |
|--------------|-------------------------|
| 1:绿色(Green) | 7:透明色 (Transparent) |
| 2:蓝色(Blue) | 8:白色(White) |
| 3:黑色(Black) | 9:黄色(Yellow) |
| 4:灰色(Grey) | Y:多种颜色 (Mixed color) |
| 5:橙色(Orange) | |
| 6:红色(Red) | |

P=2.50mm, N为孔位数(N for hole digits), 有效位数为(Significant Digits): 02p-24p

| N | 02P | 03P | 04P | 05P | 06P | 07P | 08P | 09P | 10P | 11P | 12P | 13P |
|---|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| L | 5.60 | 8.10 | 10.60 | 13.10 | 15.60 | 18.10 | 20.60 | 23.10 | 25.60 | 28.10 | 30.60 | 33.10 |
| B | 2.50 | 5.00 | 7.50 | 10.00 | 12.50 | 15.00 | 17.50 | 20.00 | 22.50 | 25.00 | 27.50 | 30.00 |
| N | 14P | 15P | 16P | 17P | 18P | 19P | 20P | 21P | 22P | 23P | 24P | |
| L | 35.60 | 38.10 | 40.60 | 43.10 | 45.60 | 48.10 | 50.60 | 53.10 | 55.60 | 58.10 | 60.60 | |
| B | 32.50 | 35.00 | 37.50 | 40.00 | 42.50 | 45.00 | 45.50 | 50.00 | 52.50 | 55.00 | 57.50 | |

| | | |
|---|-----------------------|---------------|
|  东莞市澳斯电子有限公司 DONGGUAN AOSI ELECTRONICS CO., LTD. | 公差范围(Tolerance Range) | |
| | 150~ | ±1.5' |
| 型号(Type): FPS1-XX-250-00-YY | 60~150 | ±1.0' |
| | 30~60 | ±0.6' |
| 核准(Approval): | 6~30 | ±0.4' |
| | 0~6 | ±0.2' |
| 核审(Audit): | 角度 X | ±2' |
| | 单位(Units):mm | (Angle) X.X |
| 设计(Design): | 比例(Scale):FULL | 版次(Version):1 |